RETURN TO INDEX

RCP2660 - Hydraulic Parallel Arm

75 HP Min. - Minimum Tractor Weight: 8000 lbs.



Gearbox: 540 or 1000 rpm Cutting Width: 58" Hitch: Cat. 2 & 3, Clevis Type Lower Hitch Deck Thickness: 10 Gauge Minimum Cutting Height: 2" \$20,040 Cutting Capacity: 2" Diameter

Stump Jumper: 3/16" x 21" Round, Dish Shaped Blade Holder: 1" x 4"; Blades: 1/2" x 4" Blade Bolt: Keyed w/Hardened Flat Washer & Lock Nut Blade Tip Speed: 15,000 fpm Blade Rotation: Clockwise Horizontal Cutting Reach: 15'6" Maximum Vertical Cutting Reach: 11'5" Maximum Below Ground Level Reach: 9'1" Maximum Operating Tilt Arc: 180 Degrees 2 Parallel Arm Cylinders with Hoses & Fittings One Deck Cylinder with Hoses & Fittings Hydraulic Outlets Needed: See specific model One Hydraulic Breakaway with Reset
Transport Width: 10'1" Minimum
Driveline: Cat. 2
High Efficiency PTO Pump
Hydraulic Oil Capacity: 35 Gallons (Not included)
Hydraulic Oil Flow: 15 gpm
Overload Protection: Relief Valve One Hydraulic Breakaway with Reset

Now Available with Self Contained Hydraulic System

Oil Pressure Gauge Return Line Filter Tank Shut-Off Valve Breather Cap/Dip Stick 2 Parking Stands Auxiliary Weight Rack Flow Control Valve

Case Drained Deck Motor

For 1000 RPM, change prefix to RCPM

MODEL			APPROX. MACHINE	SHIPPING	LIST
NUMBER	DESCRIPTION	Market Committee	WEIGHT	WEIGHT	PRICE
	UTILIZING THE TRACTOR'S HYDRAULIC SYSTEM		or community		
RCP2660-01	26 SERIES - 60" Width - 540 RPM		1690#	1690#	
	HYDRAULIC DRIVEN PARALLEL ARM ROTA	ARY CUTTER			
	Front & Rear Chain Guards	Calledon Plantalanilla			
	Solenoid and Flow Control Valve for Operating (one set of outlets needed for this, and one si	TO A PROCESSION OF AN ACCOUNT OF THE PROCESSION			
	26 SERIES - 60" Width - 540 RPM	at needed for mydraunc breakaway)	1690#	1690#	
RCF 2000-02	HYDRAULIC DRIVEN PARALLEL ARM ROTARY CUTTER		1090#	1050#	
	Front & Rear Chain Guards	THE STATE STATES			
	Hydraulic Hose Package for Hook-Up Direct to	Tractor Hydraulics			
	(3 sets of outlets needed for this, and one :	set needed for Hydraulic Breakaway)			
RCP2660-03	26 SERIES - 60" Width - 540 RPM	SERIES - 60" Width - 540 RPM 1690		1690#	
	HYDRAULIC DRIVEN PARALLEL ARM ROTARY CUTTER				
	Front & Rear Chain Guards, Float Valve				
	Solenoid and Flow Control Valve for Operating Cylinders Electrically				
	(one set of outlets needed for this, and one se	et needed for Hydraulic Breakaway)	i		
	SELF-CONTAINED HYDRAULIC SYSTEM				
RCP2660-05	26 SERIES - 60" Width - 540 RPM		1690#	1690#	
	HYDRAULIC DRIVEN PARALLEL ARM ROTARY CUTTER				
	Front & Rear Chain Guards, Sciencid Operates				
	(One set of outlets needed for Hydraulic Breakaway)				
RCP2660-06	26 SERIES - 60" Width - 540 RPM	DV CHITED	1690#	1690#	
	HYDRAULIC DRIVEN PARALLEL ARM ROTARY CUTTER Front & Rear Chain Guards, Float Valve, Solenoid Operates Cylinders Electrically				
	(One set of outlets needed for Hydraulic Breakaway)				
ADD OPTION NO.	YOU MAY CHOOSE				
-10	Gauge Wheels (available with Options 02, 03	8 06	230#	230#	
	2 Front and 1 Rear 13" x 5" Semi-Solld Gauge Wheels*		220#	25011	
	This option allows the cutting deck to follow the contour of the ground				
-55	Kubota 3-Point Stabilizer Kit (316-325A) must be	used on M126GX, M135GX, M6-131 & M6-141 Tractors	135#	135#	
	Kubota Daalers: RCP26 ONLY fits M126GX, M135GX, M6-131, M6-141, and M7 Tractors				
	YOU MUST ADD ONE WEIGHT BRACKET				
-70	For John Deere Weights (316-230A)		63#	63#	
-71	For Case Weights (316-231A)		72#	72#	
-72	For IH Weights (316-232A)		53#	53#	
-73	For Case IH Weights (316-233A)		64#	64#	
-74	For New Holland Weights (316-234A)		80#	80#	
-75	For Kubota Welghts (316-276A)		000		
ACCESSORY	The second second second				
16-063A	Debris Guard - for use with tractors without a	cah.			
10-003A		Can			
	Availabla in Buckskin Only				

NOTE: Use of Quick Hitch on some tractors may require longer driveline. Gearbox HP rating is based on in field use and performance

LAND PRIDE PRICES EFFECTIVE DECEMBER 1, 2018

P. 69

U.S. FUNDS